



## FE60

FE60 is a soft and flexible wire designed for multiple applications in electrical and infrastructure projects. It is primarily used as a stay wire for poles to ensure stability and safety, but also performs effectively as a top wire and guard wire.

Its flexibility makes FE60 easy to handle and install, while maintaining reliable performance over time. A versatile solution for professional applications where ease of installation and dependable functionality are essential.

## APPLICATION

FE60 is a soft and flexible wire designed for multiple applications in electrical and infrastructure projects. Primarily used as a stay wire for poles, it ensures stability and safety, but it also serves effectively as a top wire and guard wire. Thanks to its flexibility,

FE60 is easy to handle and install, while maintaining reliable performance over time. A versatile choice for professional use where ease of installation and functionality are essential.

## STANDARDS

### Conductor

SEN 240804



Name	E-Number	Cross section [mm <sup>2</sup> ]	Number of strands [pcs]	Strand diameter [mm]	Lay direction	Outer diameter [mm]	Total weight [kg/km]	Maximum breaking load [kN]
Fe60-16/2,3	0620005	16	7	1.71	Right	5.1	126	9.45
Fe60-16/5,3	0620004	16	3	2.6	Right	5.6	125	9.39
Fe60-25	0620006	25	7	2.12	Right	6.4	194	14.6
Fe60-33		33	7	2.44	Right	7.3	257	19.3
Fe60-52	0620007	52	7	3.08	Right	9.2	409	30.7

This document is automatically generated and is to be used as a guide only. May contain theoretical data. Images are for illustrative purposes only. No liability is accepted following the use of this data. Changes may be made without prior notice. It is the responsibility of the end user to determine suitability for any given application. E&OE. Copyright ©2026 Amokabel. All Rights Reserved.