



ALUTRACK

Alutrack 70 AL-W is an aluminium grounding cable designed for power distribution installations. It is suitable for fixed installation both indoors and outdoors and can be laid in air as well as in soil, ensuring reliable and long-term performance.

The cable is halogen-free, enhancing fire safety by reducing smoke emissions and eliminating corrosive gases in the event of fire. In addition, Alutrack 70 AL-W is fully recyclable and has a low scrap value, making it an economical and environmentally sustainable solution.

APPLICATION

Alutrack 70 AL-W is an aluminium cable for earthing. The cable is intended for electrical distribution installations and for fixed installation indoors and outdoors, in air and in the ground. Recyclable with low scrap value. Halogen-free.

STANDARDS

Material

EN 50363-8

Conductor

EN 60228

Construction

EN 61394

EN 50182, CASE 4

CONSTRUCTION

Outer sheath

PE

PROPERTIES

Max. continuous temperature

70

Max temperature

70 °C

PROPERTIES

Min. temperature

-20 °C



Name	Construction	Cross section [mm ²]	Conductor diameter [mm]	Insulation thickness [mm]	Outer diameter [mm]	Total weight [kg/km]
70 AL-W	37 x 1,62 AlMgSi	76.2	11.5	1.7	14.9	304

This document is automatically generated and is to be used as a guide only. May contain theoretical data. Images are for illustrative purposes only. No liability is accepted following the use of this data. Changes may be made without prior notice. It is the responsibility of the end user to determine suitability for any given application. E&OE. Copyright ©2026 Amokabel. All Rights Reserved.